# Wild Bunch Match Rules

### Firearms:

- Handgun: Full size Single stack steel frame 1911 style semi□auto pistol in 45 ACP caliber.
- Rifle: Any SASS legal main match rifle in 40 caliber or larger.
- Shotgun: Winchester '93/'97 and/or the Model 12 pump 12 gauge shotgun, civilian or military style.

#### **Ammunition:**

- Handgun: Minimum bullet weight 180 grns. Minimum power factor 150. Max velocity 1000fps.
- Rifle: Minimum bullet weight 180 grns. Minimum power factor 150. Max velocity 1400fps.
- Shotgun: Standard velocity #6 lead shot or smaller.
- All other SASS main match ammunition requirements must be met.

### **Firearm Covenants:**

### **Traditional Handgun**

- Must be shot one handed, unsupported. Weak hand may be used for loading, racking slide and in case of malfunctions.
- Barrel length must be 5 inches. No barrel porting or compensators or other recoil reducing devices.
- Barrel with standard barrel brushing. No "Bull" barrels.
- Magazine wells may be beveled, but may not be oversized, extended or flared.
- Only non-adjustable dovetail rear sights and blade type front sights.
- No sight inserts or colored sights. Sights must be black or blued.
- Stainless steel is permitted.
- Grips must be "GI" style wood or plastic. Other natural materials allowed, but no rubber grips. No target style or thumb rests.
- Only rear slide may be checkered or serrated. (None on front slide)
- No external "ribbing" or "ribs" on top of slide.
- Magazines must be of standard length and may not hold more than 8 rnds. No extended base pads.
- Only standard grip safeties. No beavertail style grip safeties.
- Standard length magazine release. (May not be extended or oversized).
- Standard length thumb safeties and slide releases. (No extensions).
- Standard recoil spring and guide. No full length guide rods. Short or long solid trigger allowed
- Flat or arched mainspring housings allowed. Lowered and flared ejection port allowed only if factory original. Standard ejection ports may NOT be modified.
- No checkering on front strap or trigger guard. Standard spur type hammers only.
- Internal accurizing and action tuning is permitted.

**NOTE:** "Standard" in all cases refers to Standard Military Specifications

### **Modern Handguns:**

- May be shot using any shooting style.
- Barrel length must be 5 inches. No barrel porting or compensators or other recoil reducing devices.
- Barrel with standard barrel brushing. No "Bull" barrels.
- Magazine wells may be beveled, but may not be oversized, extended or flared.
- Adjustable or non-adjustable dovetail rear sights and blade type front sights.
- Colored inserts or dots permitted. No optical or fiber-optic sights.
- Stainless steel is permitted.
- Grips must be wood or plastic or other natural materials. No target style or thumb rests.
- Front and rear slide checkering and serrations, and "ribbing" or "ribs" on top of slide permitted.
- Magazines must be of standard length and may not hold more than 8 rnds. No extended base pads.
- Extended beavertail grip safeties permitted.
- Magazine release may be extended, but NOT oversized.
- Thumb safeties and slide releases may be extended. Thumb safeties may be ambidextrous.
- Full length recoil spring guide rod, and lowered and flared ejection port allowed.
- Lanyard loop is optional. Match trigger and checkering on front strap or trigger guard permitted.
- Lightweight competition style hammer permitted.
- Internal accurizing and action tuning is permitted.
- Flat or arched mainspring housing, internal accurizing and action tuning permitted.

#### Rifle:

• Must meet SASS main match requirements and be 40 caliber or larger.

### Shotgun:

• Must meet SASS main match requirements for pump shotgun, except that military configurations are permitted. Must be 12 gauge.

# Holsters, Cartridge Belts, Magazine Pouches and Bandoliers:

- Holsters and magazine pouches must be of traditional or military design and made from traditional materials. (e.g. canvas or leather).
- Holsters must cover the entire barrel and completely cover the ejection port. No open front speed holsters allowed.
- Holster flaps and straps need NOT be closed during competition.
- No metal or plastic "competition" type equipment allowed.
- No shoulder or cross-draw may be used during competition.
- Magazine pouches must be worn vertically, and may hold either one or two magazines.
- At least 2 inches of the magazine must be covered by the magazine pouch.
- All other SASS regulations pertaining to these items apply.

# **Costuming:**

Recommendations: Period US Military from 1900 to 1916 or period western dress similar to that
worn by "Pike", "Dutch", "Lyle" or "Tector" in the closing scene of the Wild Bunch movie. Western
style pants with suspenders and long sleeve shirt. Vests are optional. Jean are NOT recommended.
Boots must be SASS legal. Hats must be worn, and must be of felt. NO straw hats. Any SASS legal
western clothing is considered the absolute minimum.

### **Firearms Rules and Penalties:**

- The pistol is discarded in a safe condition. It may have an empty magazine or a loaded magazine, or no magazine. After first being charged it is never re-holstered until cleared at the end of the stage by the RO/TO.
- Magazines may be loaded at any time.
- Magazines shall be loaded with 7 rounds maximum.
- Dropped or unloaded magazines may be picked up and reused.
- Movement is allowed with the 1911 in hand with the slide closed on an empty chamber with no magazine or a loaded/empty magazine until the pistol is first charged during the stage.
- When moving with the 1911 in hand, after the pistol has been charged, the Trigger Finger must be outside the trigger guard. (MSV)
- No cocked, loaded pistol may ever leave a shooter's hand. (SDQ) This does not apply to clearing malfunctions.
- Changing magazines on the move is allowed as long as the Trigger Finger remains outside the trigger guard. Once the slide moves into battery and a live rounds is in the chamber the "basketball travelling rule" is in effect. (Trigger Finger-MSV. Slide closed on a live round-SDQ)
- At the end of the course of fire the 1911 must be shown clear on the firing line. At the end of the course of fire and before holstering the 1911 pistol, the following RO/TO commands shall be used:
  - Show clear chamber and no magazine.
  - Slide Forward- slide forward into battery
  - Hammer down- pistol pointed safely down range and pull the trigger allowing the hammer to fall unimpeded.
  - Holster. Pistol safe in holster.
- Shotgun magazines may be loaded with the number of rounds required for the initial target sequence. Any additional rounds needed must be loaded from the body or other specified staging position. Any rounds loaded beyond the required number that are fired are treated as "illegally acquired ammunition."
- Rifles should be loaded with the number of rounds required by the initial target sequence at the
  loading table with the hammer either on the safety notch or fully down on an empty chamber. Any
  additional rounds must be loaded from the body or other specified staging position. Any rounds
  loaded beyond the required number that are fired are treated as "illegally acquired ammunition."
- Loaded long guns must be staged with the muzzle pointed down range, the action closed, the chamber empty and the hammer either on the safety notch or fully down. (Failure to comply-SDQ)
- All other SASS Rules pertaining to handling firearms apply.

# Shooting Procedures, Rules and Penalties Specific to Wild Bunch Match

### Operations at the loading table:

- A loaded magazine may be inserted in the handgun, the slide is NOT to be cycled, and the handgun holstered. (Magazine not inserted – NO CALL. Slide cycled – SDQ unless corrected before leaving the shooter's hands)
- The shotgun magazine will be loaded after closing the action and lowering the hammer on an empty chamber. (Failure to load NO CALL. Closing action after loading –SDQ, unless corrected before leaving shooter's hands)
- Rifle handling as per normal SASS Rules.

## On the firing line:

• Unless specifically called for by the stage description, a live round will be chambered in the handgun on the clock when needed in the firing sequence.

# Operations at the unloading table:

• The handgun should have already been cleared on the firing line, as per previous instructions contained herein. The already cleared handgun should remain holstered. Shotguns and rifles are to be cleared as per normal SASS Rules.

Page 4 of 4